


SEEKER™

Crossing Support Catheter

SEEKER® CROSSING SUPPORT CATHETER

.018" x 150cm



RECOMMENDED GUIDEWIRE	WORKING LENGTH	RECOMMENDED INTRODUCER	MARKER WIDTH	MARKER SPACING	TOTAL MARKER LENGTH
.018"	150cm	4F	1cm	1cm	30cm

BAIRD | VASCULAR

SEEKER® Crossing Support Catheter

ENGLISH

INSTRUCTIONS FOR USE

CAUTION: Federal (U.S.A.) Law requires that this device be used only by or under the direct supervision of a physician.

Device Description
The Seeker® Crossing Support Catheter is a catheter with a radiopaque marker band and a catheter tip designed to facilitate advancement of the catheter into the vessel and prevent retrograde flow.



The over the wire catheter is composed of 40, 60, 135, and 150 cm working lengths. The catheter is designed for use in the 10cm and 20cm catheters and are positioned 5-8cm from the distal tip.

Reference Table 1 for Seeker® Catheters

Seeker® Catheter	Working Length	Marker Band	Marker Spacing	Marker Width	Marker Length
40cm	40cm	1cm	1cm	1cm	30cm
60cm	60cm	1cm	1cm	1cm	30cm
135cm	135cm	1cm	1cm	1cm	30cm
150cm	150cm	1cm	1cm	1cm	30cm

Indications for Use

The Seeker® Crossing Support Catheter is designed for use in the 10cm and 20cm catheters and are positioned 5-8cm from the distal tip.

Contraindications

None known.

Warnings

1. Contains supplied STERILE. The device is supplied in a sterile container and should be used as such.
2. This device has been designed for use in the 10cm and 20cm catheters and are positioned 5-8cm from the distal tip. The residue of blood or debris which may lead to infection or thrombosis of the vessel.
3. Do not reinsert the catheter into the vessel after it has been removed. The catheter is designed for single use only.
4. When the catheter is inserted into the vessel, the catheter should be inserted under high magnification. The catheter should be inserted into the vessel and the catheter should be inserted into the vessel.
5. While retracting the catheter, the catheter should be retracted slowly and the catheter should be retracted slowly.
6. After use, this product may be disposed of in a sharps container.
7. Exceeding the maximum length of the catheter may result in damage to the catheter.

Precautions

1. Carefully inspect the catheter for any damage or defects before use. Do not use if damaged or defective.
2. The catheter should be used in the 10cm and 20cm catheters and are positioned 5-8cm from the distal tip.
3. The catheter should be used in the 10cm and 20cm catheters and are positioned 5-8cm from the distal tip.
4. Only use catheters of the same size and type as the catheter being used.
5. Do not use the catheter in the 10cm and 20cm catheters and are positioned 5-8cm from the distal tip.
6. Do not use the catheter in the 10cm and 20cm catheters and are positioned 5-8cm from the distal tip.
7. Do not use the catheter in the 10cm and 20cm catheters and are positioned 5-8cm from the distal tip.
8. Do not use the catheter in the 10cm and 20cm catheters and are positioned 5-8cm from the distal tip.
9. Do not use the catheter in the 10cm and 20cm catheters and are positioned 5-8cm from the distal tip.
10. Do not use the catheter in the 10cm and 20cm catheters and are positioned 5-8cm from the distal tip.